

SURE

VB5S6 / VB5C6



SUBMERSIBLE CAMERA

Submersible camera supplied with lens, bracket and 30 metres of cable

Ideal for drains, ponds or extreme weather conditions

Total Depth - 50 feet
Angle of View - 70 Degree
Body Material - Stainless Steel

VB5S6 - Monochrome Version

VB5C6 - Colour Version

Key Specification

- CCD 1/3" Sony HAD
- Resolution 420 TVL Lines
- Lux 0.05
- Lens 3.6mm
- Power 12V DC
- Dimensions 32mm dia x 110mm
- Suitable for Internal/External use
- IP68

For orders or more information please contact us on:

**tel: 01949 836990 fax: 01949 836991 email: sales@sure24.net
or visit our website www.sure24.net**

VB5S6 / VB5C6

SPECIFICATIONS:

TECHNICAL <i>(for colour version only)</i>	
Image Sensor (device)	SONY Interline Transfer Hyper HAD CCD
Image Size	1/3"
Picture Element (effective)	500 x 582 (h x v)
Optical Black Elements	Horizontal: 3:in front, 40:in back, Vertical: 12:in front, 2:in back
Chip Size	6.0 x 4.96mm (h x v)
Synchronising System	Internal Sync
Interlace	2:1 Interlace
Horizontal Resolution	420 TVL
Aperture Correction	H aperture V aperture
Video Output Level	1.0V (p-p) (75 ohms, composite)
Video S/N Raton	More than 50dB (AGC Off)
Min Illumination	0.05 Lux (F2.0) AGC On
White Balance	ATW large range: 2400K to 11000K
Electronic Iris	Setting ON
Auto Exposure system	Auto electronic iris: 1/50 (1/60) - 1.100000 sec
Back Light Compensation	Active Histogram Plus window weight BLC
Gamma	0.45
Built-in Lens	Board Lens 3.6mm. Fixed Iris F2.0
Operating Temp	-10°C ~ +50°C
Storage Temp	-20°C ~ +70°C
Power Supply	DC +12V (W/Adaptor)
Power Consumption	3W
Dimensions	110mm x 32mm dia
Plug	Red Plug: DC+12V input. Yellow Plug:Video Out
Accessories	Video- RCA+BNC, power DC-jack, 100 feet cable Mouting Bracket Adaptor: AC230V input/output Regulator DC+12V/300mA

SURE 24 Limited
SURE House,
2 Moorbridge Court,
Bingham,
Notts. NG13 8GG

tel: 01949 836990
email: sales@sure24.net
fax: 01949 836991
web: www.sure24.net

SURE
... innovations for a safer world